

RH613 DAY CAB



Configuration: 113" BBC
Cab: Day cab
Engine: International® A26



- ▶ Local or Regional Applications
- ▶ Van, Bulk, Flatbed or Specialty Haul
- ▶ Fleet or Owner Operator
- ▶ Pick up and Delivery

The new International® RH™ Series is built to redefine the rules for productivity. Its tight turning radius, wide-ranging visibility and smart new driver-centric cab allow confident maneuvering through tight city streets and cramped loading docks, making it ideal for beverage haul, tanker and other applications. The RH Series features the International A26, a 12.4L engine that's born from a new way of thinking and proven to deliver optimal uptime and class-leading fuel efficiency while reducing weight.





KEY FEATURES:

- ▶ 113" BBC and up to a 50° wheel cut for excellent turning radius and maneuverability
- ▶ Sloped, short hood provides excellent driver visibility on congested city streets and delivery applications
- ▶ Side glass and mirror designs improve lateral visibility and reduce neck strain
- ▶ All-new dash designed for the driver with controls and switch placement optimized by use
- ▶ Bendix® Wingman® Advanced™ Collision Mitigation is standard on RH Series
- ▶ 12.4L International A26 engine is engineered with proven components for maximum uptime
- ▶ Available premium gauge cluster designed with driver input is customizable with virtual gauges
- ▶ Easy-access column-mounted shifter integrated with engine braking helps keep hands on the wheel
- ▶ New industry-standard J1939 electrical system architecture and improved harnessing to maximize uptime
- ▶ All-new HVAC system designed for reliability, now includes a high-performance MAX defrost feature



113" BBC SET-BACK FRONT AXLE

GVW

- ▶ 32,000 - 60,000 lbs.

Models/BBC/BA

- ▶ 113" BBC / 50" BA

Wheelbase Options

- ▶ 146 - 226" 4x2
- ▶ 152 - 240" 6x4

Axle Configurations

- ▶ 4x2, 6x2, 6x4

Rear Axle

- ▶ SINGLE REAR AXLE (4x2)
 - Meritor: 23,000 lbs.
 - Dana Spicer: 23,000 lbs.
- ▶ TANDEM REAR AXLE (6x4)
 - Meritor: 40,000 - 46,000 lbs.
 - Dana Spicer: 40,000 - 46,000 lbs.

Front Axle

- Hendrickson: 12,000 - 14,000 lbs.
- Dana Spicer: 12,000 - 14,000 lbs.
- Meritor: 12,000 - 14,000 lbs.

Frames

- ▶ Heat Treated Alloy Steel 120,000 PSI

Front Suspension

- ▶ Spring Monoleaf: 12,000 - 13,200 lbs.
- ▶ Parabolic Taperleaf: 12,000 - 14,000 lbs.

Rear Suspension

- ▶ AIR SINGLE
 - International®: 20,000 lbs.
 - International: 23,500 lbs. Vari-rate spring
- ▶ AIR TANDEM
 - International: 40,000 lbs.
 - Hendrickson: HTB 40,000 lbs.
 - Hendrickson: HAS 46,000 lbs.

Electrical System

- ▶ ALTERNATORS
 - Bosch: 12 Volt, 160, 165, 200 Amp
 - Leece-Neville: 12 Volt, 160, 210, 240, 325 Amp
 - Delco Remy: 12 Volt, 165, 200, 300 Amp
- ▶ BATTERY SYSTEMS
 - International®: 12 Volt 1950 - 3700 CCA
 - JCI: 12 Volt 2250 - 3000 CCA
 - Deka: 12 Volt 2800
 - Fleetrite®: 12 Volt 2800 - 5600 CCA
 - EnerSys Odyssey: 12 Volt 3450 - 4600 CCA

Exhaust System

- ▶ Single canister after-treatment device
- ▶ Frame Mounted Right Side, Under Cab
- ▶ Includes Horizontal or Vertical Tailpipe and Guard; Optional Bright Tailpipe and Guard

Brakes

- ▶ Air Drum Brakes with ABS with Optional Automatic Traction Control and Electronic Stability Control
- ▶ Air Disc Brakes with Automatic Traction Control, and Electronic Stability Control

Power Steering

- ▶ Sheppard
- ▶ TRW

Engines

- ▶ International® A26: 370 - 450 hp and 1,350 - 1,750 lb.-ft. of torque

Transmissions

- ▶ Eaton®: 10, 13, 15, 18-Speed Manual
- ▶ Eaton UltraShift® PLUS: 13, 18-Speed Automated Manual
- ▶ Eaton Fuller Advantage™ Series: 10-speed
- ▶ Eaton UltraShift PLUS LSE 16-speed Transmission

Fuel Tanks

- ▶ 70 - 120 Gallon, Dual, Non-Polished or Polished Aluminum, Mounted Back of Cab
- ▶ 70 - 100 Gallon, Single, Non-Polished or Polished Aluminum, Mounted Back of Cab

Tires

- ▶ Continental, Michelin, Bridgestone, Goodyear

Note: The information and conclusions contained herein are believed to be correct at time of publication, but do not necessarily apply to similar vehicles with different specifications or with production dates after the production of this publication. Vehicles with different specifications or later dates of production may yield different results. Vehicle specifications are subject to change without notice. TAD17009 04/2017 ©2017 NAVISTAR Inc. All rights reserved. All marks are trademarks of their respective owners.